



Manufacturer of made-to-measure agricultural trailers since 1945

ARBORICULTURAL TRAILERS

HYDRAULIC FRUIT TRAILERS



Standard equipment :

- Complete lighting
- Removable front board
- 2 mini-winches

OPTIONS :

- Swinging arm

Platform elevation range	Length	Width	Wheels
0.60	4.20	1.25	10/15
1.20	4.20	1.25	10/15

HYDRAULIC FRUIT TRAILER WITH WAY OF BEARING



HYDRO-PNEUMATIC FRUIT TRAILER

Equipped with two bellows to improve the suspension.



Operating principle :

The crates of fruit are placed on the pallets which are within the chassis. For greater ease of loading, the height of the loading platform is adjusted to the required height. After having been completely loaded, either the platform is lowered to the ground and the pallets are removed by a pallet truck, or the trailer platform is raised to the level of a loading bay or a lorry, up to 1m20, to make unloading by pallet truck possible. All the jacks are operated by a distributor controlled from the tractor seat .

HYDRAULIC FRUIT TRAILER WITH DISTRIBUTOR AT ELECTRIC CONTROL



TRAILER FOR THE TRANSPORT OF PALLET



BIN LOADING MACHINE

Characteristics :

Load capacity :
12 to 15 bins.

Internal dimensions of the chassis :

Width : 1.25m

Length : 5.20m

Overall width : from 2.10m to 2.49m, depending on the tyres.

Equipped with 4 wheels mounted on swinging arms. In this way the trailer has great flexibility, both in the orchards and on the road.

These swinging arms attached to an articulated arm operated by two hydraulic jacks, make it possible to raise the trailer for transport, all this being linked to a large cross-section tubular chassis.

The drawbar is also articulated, adjusted by a double-action jack, thus keeping the load horizontal. All the hydraulic circuit is by a distributor with 4 levers operated from the tractor seat.

Operating principle :

First of all, the bins are taken out from between the rows of fruit trees.

They are lined up in groups of 12 to 15.

After having removed the rear cross-piece, which holds the two forks in place during transport, manually or hydraulically, the bin loading machine is backed off.

The 2 forks are slid under the bins, and the hydraulic door can now be closed.

Then the 3 jacks can be put under pressure to lift the trailer platform to the desired height (maximum elevation 0.50m).

OPTIONS :

- Bin pusher
- Electric control (panel)



NORMAL FRUIT TRAILERS FOR TRANSPORTING PALLETS OR BINS OF FRUIT



Standard equipment :

- Lighting incorporated in the rear cross-member.
- Retractable dolly wheel.
- Removable front board.
- Dropping tailboard for unloading at a loading bay.
- Front mini-winch on the top of the board.

Platform width	Platform length	Height above ground	Wheels
1.05	3.70	0.40	215*15
1.25	4.10	0.40	10.0/15
1.25	5.20	0.40	10.0/15
1.25	6.20	0.40	10.0/15

OPTIONS :

- Swinging arm.
- Caterpillar door tipping.
- Loading ramp.

FRUIT TRAILER WITH LOADING RAMPS



PLATFORM TRAILER CARRY CHARIOT



FRUIT TRAILER WITH VAT



MARKET GARDENER TRAILER



FRUIT TRAILER WITH SPRINGLEAF AND DROPSIDES



PNEUMATIC FRUIT TRAILER 4 SWINGING ARM WHEELS



PNEUMATIC SUSPENSION FRUIT TRAILER MODEL ATOM (6 PALLETS)



LOW-SLUNG SPREADERS

A NEW DISTRIBUTION SYSTEM

- Makes it possible to spread on the right side of the spreader over a width which varies with the speed of the power take-off (0.50m to 2m).

- This also makes for economizing fertilizer by the width of the body, and a better distribution at the feet of trees.



OPTIONS :

- Movement reverser
- Bogie swinging arm for the 4m and longer models.
- Vertical rotors
- Projection shutters
- Sloping heightening plates



Body length (m)	Body width (m)	Total height	Overall width	Dropside height	Load height
2.50	1	1.50	1.45	0.50	0.85
3.00	1.30 ou 1.55	1.50	1.85 ou 2.10	0.50	0.85
3.50	1.30 ou 1.55	1.50	1.85 ou 2.10	0.50	0.85
4.00	1.30 ou 1.55	1.55	1.85 ou 2.10	0.50	0.85

double rotors

THE MARKET GARDENING

Hydraulic fruit trailer at variable level



Special trailer for market gardener :
transport of salad in bin

Compost spreader for standing gangplank type REV2 2500



Standard equipment :

- One-piece body
- Length 3 m (interior) and more
- Weidth 1m10 (interior) max.for 2 rotors (or 1m60 for 4 rotors)
- Dropsides 0.60
- Overall width of wheel 1m79
- Interior width of wheel 1m25
- Total height 1m65
- Hydraulic feed of conveyor belt,adjustable by screw
- 2 horizontal rotors
- Spreading table at 2 rotors



- Back cover for funneling of compost on the width of body
- Directional axle
- Wheel 10.75/15
- Hitch on lift arm and power take off wide-angle lens, machine side
- Dolly wheel
- Lighting
- Hydraulic control by a distributor 2 elements DE one of which with adjustable outflow for conveyor belt
- Spreading table for greenhouse,tunnel,and big width

DO YOU NEED SPECIAL MODELS?

All our catalogues are not exhaustive.
On request, we can adapt our models to
the dimensions which you require!

Website : www.roche-trailers.com - E-Mail : contact@roche-trailers.com
Design & production : [Eric CHAUVIN](#)
