



Manufacturer of made-to-measure agricultural trailers since 1945

COMPOST AND MANURE SPREADERS

Manure and compost spreader for vineyards

Narrow design for getting through between closely planted rows of vines.

Standard equipment :

- Dolly wheel
- Adjustable height coupler head
- Lighting
- Fixed ring
- Protection grille
- Universal joint

OPTIONS :

- Directional axle making it easier to get out from between the rows, helps avoid slipping in vineyards on hillsides
- Hitch on a lift arm so as to be able to turn in the shortest turning areas
- Shutters for adjusting the width of the spreading
- Distributing cover to channel the product over the width of the row
- Variable-track axle to ensure better stability
- A choice of wheels to avoid compacting the soil
- Turning ring- Continuous hydraulic feed, making it possible to spread small quantities per hectare



Manure spreader for wine-growers
Flared body in one piece



DO YOU NEED SPECIAL MODELS ?

All our catalogues are not exhaustive.

On request, we can adapt our models to the dimensions which you require !

TYPE	Live load (Kg)	Empty weight (Kg)	Length (m)	Int. width (m)	Overall width (m)	Conveyor belt ch Ø10	Dropside height (m)	Axle	Tyres	Brake	Support
REV 2 1500	1500	600	2.50	0.80	1.07	2 ch	0.60	50	200/60*14,5	mec.	Dolly wheel
REV 2 1800	1800	620	2.50	1.00	1.27	2 ch	0.60	50	205/15	mec.	Dolly wheel
REV 2 2500	2500	850	3.00	1.30	1.57	2 ch	0.60	50	10*15	mec.	Dolly wheel

Manure and compost spreader for arboriculture, market gardening and mountain areas

Because of its low-profile design, the spreader can pass underneath the main branches of fruit trees, or go through a market gardening tunnel.

Low-slung spreaders

A NEW DISTRIBUTION SYSTEM

- Makes it possible to spread on the right side of the spreader over a width which varies with the speed of the power take-off (0.50m to 2m).

- This also makes for economizing fertilizer by the width of the body, and a better distribution at the feet of trees.



OPTIONS :

- Vertical rotors for spreading across the whole width of the row
- Sloping heightening plates to push up the main branches
- Continuous hydraulic feed to make it possible to spread small dosages per hectare
- Lateral spreading from the right side for spreading at the foot of the trees over an 80 cm width around the trunk
- A choice of tyres so as to avoid packing down the soil



Body length (m)	Body width (m)	Total height	Overall width	Dropside height	Load height
2.50	1	1.50	1,45	0.50	0.85
3.00	1.30 ou 1.55	1.50	1.85 ou 2.10	0.50	0.85
3.50	1.30 ou 1.55	1.50	1.85 ou 2.10	0.50	0.85
4.00	1.30 ou 1.55	1.55	1.85 ou 2.10	0.50	0.85

Double rotors

Compost and manure spreader for large-scale farming

Several sizes and load capacities.

2 spreading systems :

- Horizontal toothed rotors (Type RE2)
 - Vertical screw rotors (Type E30, E40, E55, E65, E80) :
- A new generation for spreading over a 9 m wide strip, with perfect evenness of spreading, and very high stability in mountain areas , thanks to the design of a body between the wheels (Tumbrial type).



Spreader with horizontal rotors



with or without a spreading table

2 and 4 vertical toothed or screw rotors



TYPE	Live load (Kg)	Empty weight (Kg)	Length (m)	Int. width (m)	Overall width (m)	Conveyor belt ch Ø10	Dropside height	Axle	Tyres	Brake	Support
RE2 3500	3500	1050	3.30	1.60	1.87	2 ch	0.50	60	10*15 10 ply	mec.	Dolly wheel
RE2 4000	4000	1240	3.50	1.80	2.07	2 ch	0.50	60	10*15 10 ply	mec.	Jack leg
RE2 4001	4000	1380	4.00	1.80	2.07	2 ch	0.50	60	11.5/15 14 ply	mec.	Jack leg
RE2 4800	4800	1490	4.00	1.80	2.07	2 ch	0.50	60	11.5/15 14 ply	mec.	Jack leg
RE2 5500	5500	1600	4.00	2.00	2.27	4 ch	0.50	70	13.5/75430.9	hyd.	Jack leg
RE2 6500	6500	1750	4.00	2.00	2.27	4 ch	0.50	70	13.5/75430.9	hyd.	Jack leg
RE2 8000	8000	2000	4.50	2.00	2.27	4 ch	0.50	80	15.22.5	hyd.	Jack leg

Double rotors with inclined screws

Standard equipment :

- Low-slung flared body
- Tubular chassis
- Lighting
- Conveyor belt driven by 2 \varnothing 12HR chains from model E40 and up
- Front protection grille
- Hydraulic feed from the tractor with cross-width distribution of the outflow

OPTIONS :

- Sprung drawbar
- Hydraulic support
- Hydraulic door
- Low-pressure tyre
- Tractor-profile tyre
- Hydraulic power unit
- Hydraulic distributor, electric control panel
- Shutters

NOUVELLE GENERATION



Type	Live load	Empty weight	Body	Overall width	Dropside height	Load height	Cubic capacity	Wheels	Axle	Support	Brake	V-shaped drawbar	Screw \varnothing	Total height
E 30	3.2T	1260	3.50*1.26	1.93	0.70	0.95	4.10m ³	11.5/15	606	screw	hyd.	adjustable	\varnothing 650	1.75m
E 40	4 T	1720	3.80*1.26	2.05	0.85	1.05	5.10m ³	13.5/75430.9	706	screw	hyd.	fixed	\varnothing 650	1.95m
E 55	5.5T	2200	4.25*1.26	2.36	1.10	1.30	7.00m ³	20.0/70.508	708	screw	hyd.	fixed	\varnothing 650	2.35m
E 65	6.5T	2760	4.40*1.50	2.54	1.35	1.70	1.0m ³	20.0/70.508	808	screw	hyd.	fixed	\varnothing 760	2.80m
E 80	8 T	3150	5.00*1.50	2.54	1.35	1.70	2.8m ³	20.0/70.508	908	screw	hyd.	fixed	\varnothing 760	2.80m

Fertilizer and sand spreader

Totally hydraulic equipment



EEV2 all hydraulic spreader :

Used above all in vineyards because of its very narrow track of 1m15. The hopper dimensions are 2m55*1m20 2-tray spreading system. The distribution of the product to be spread is controlled by two adjustable shutters. The outflow rate can also be controlled by means of a manually controlled gate with a scale graduated in millimetres.

EEF2 spreader :

Used in arboriculture or open fields. Hopper dimensions are 3m x 1m50 Same spreading system as for the EEV2.

Standard equipment :

- Adjustable towing system
- Power take-off
- Lighting
- Variable outflow

Distribution by two discs, the orientation and the width of the spreading are controlled by simple adjustment of the deflectors.



OPTIONS :

- Heightening plates
- Grading grille
- Hydraulic opening of the door
- Hitch on a lift arm
- Low pressure wheels
- Tractor-profile tyre
- Totally hydraulic feed

TYPE	Live load (kg)	Body length	Body width	Conveyor width	Axle	Overall width	Volume	Wheels	Brakes	Support
EEV2	1500	2 m 55	1 m 20	500mm	50	1 m 26	1.3 m3	10*15	mec.	Dolly wheel
EEF2	2500	3 m	1 m 50	800mm	60	1 m 75	1.8 m3	11.5/15	mec.	Dolly wheel

EEF2 with rotor



Strawy for livestock building



Droppings spreader



Standard equipment :

- Adjustable towing system
- Power take-off with defender
- Lighting
- Turbine of projection with big debit for the manuring such as: droppings of hens, dropping of rabbits, dungs of cows, liser and transport of cereal

OPTIONS :

- Deflector
- Hydraulic brake
- Opening of the hydraulic door

TYPE	Litres	Wheels	Axle	Width	Length
ESF 3200	3200	10.0/16 10 ply	60	1,60 m	3,00 m
ESF 5000	5000	13.5/75 430.9	70	1,80 m	3,00 m

Earth spreader

Standard equipment :

- Body 2,20 m
- Overall width 1,40
- Wheel 10x15
- Mechanical and hydraulic brake
- Lighting
- Hydraulic sash door
- Electric distributor 5 functions
- Hydraulic shaft
- Conveyor belt right and left



Site web : www.roke-trailers.com - E-Mail : contact@roke-trailers.com
Design & production : [Eric CHAUVIN](#)
