



Manufacturer of made-to-measure agricultural trailers since 1945

## MULTI-PURPOSE TRAILERS



### 2-wheel balanced full trailers : rear tipping and three-way tipping models

TYPE	Live load	Empty weight	Length	Width	Dropside height	Axle	Tyres	Brake	Front support
RB 2 2500	2500	750	2.50 m	1.20 m	50	50	215*15	Mec.	Dolly wheel
RB 2 3000	3000	800	3.00 m	1.30 m	50	50	10/15	Mec.	Dolly wheel
RB 2 3500	3500	900	3.10 m	1.50 m	50	50	10/15	Mec.	Dolly wheel
RB 2 4001	4000	1050	3.50 m	1.70 m	50	60	10/15	Mec.	Dolly wheel
RB 2 4002	4000	1150	3.50 m	1.90 m	50	60	10/15	Mec.	Dolly wheel
RB 2 4800	4800	1250	4.00 m	1.90 m	50	60	11 5/15 14 ply	Mec.	Jack leg
RB 2 5500	5500	1450	4.00 m	2.00 m	50	70	135/75 430.9	Hydraul.	Jack leg
RB 2 6500	6500	1600	4.00 m	2.20 m	50	70	135/75 430.9	Hydraul.	Jack leg
RB 2 8000	8000	1900	4.50 m	2.20 m	50	80	15*22.5	Hydraul.	Jack leg
RB 2 9000	9000	2400	4.50 m	2.20 m	50	90	15*22.5	Hydraul.	Jack leg
RB 2 10000	10000	2400	4.50 m	2.20 m	50	Bogie	4RC 135/75 430.9	Hydraul.	Jack leg
RB 2 16400	12000	4500	6.00 m	2.20 m	110	Bogie	4RC 15.22.5	Hydraul.	Hyd. Sup.



**Standard equipment :**

- Adjustable-height hitch
- Metal floor
- Complete lighting
- Without backward movement
- Ribbed dropsides or one-piece body

**OPTIONS :**

- Platform extension
- Fodder lattices
- Mini-winches
- Wideners
- Cupboard-type door
- Hydraulic support
- Sprung drawbar
- Turning hitch
- Up-and-over door



**Three-way tipping trailers**

Because of their unique design, the three-way tipper have the same floor height above the ground as the rear tipper. Dropsides open upwards and downwards.



- Carrying chassis made of multiply folded metal plate joined by tubular cross-members
- Tipping structure: tubular side frames and cross pieces in 3 parts, making it possible for the floor to rest on this structure, hence avoiding all distortions of the floor.
- Tipping without backward movement
- Lighting built into the rear cross-member
- Triple-expansion hydraulic jack making for a large tipping angle

## Platform trailers for fodder



## 2-wheel trailers and 4-wheel bogie trailers bin ship and big bundle



**non-tipping  
fully balanced**

### Standard equipment :

- Metal floor
- Complete lighting
- 2 front dropside supports for the RPB 10000 and 13000 models

### OPTIONAL EXTRAS :

- Special ladder for round bales
- Rear hitch
- Fodder lattices
- Mini-winch
- Wideners
- Turning hitch
- Sprung drawbar



TYPE	Total loaded weight	Length	Width	Axle	Wheel	Brake	Platform height	Front support	Drawbar
RP 2 3000	4500 kg	3.50 m	2 m	506	10/15	Mec.	0.83	Dolly wheel	adjustable
RP 2 4000	5200 kg	5 m	2 m	606	10/15	Mec.	0.83	Dolly wheel	adjustable
RP 2 5000	5990 kg	6.10 m	2.40 m	706	11 5/15	Mec.	0.93	Dolly wheel	adjustable
RP 2 6000	7600 kg	6.10 m	2.40 m	706	135/75 430.9	Hyd.	1 m	Jack leg	adjustable
RP B 7000	8700 kg	6.10 m	2.40 m	4 demi 706	11 5/15	Hyd.	0.98	Jack leg	adjustable
RP B 7001	8700 kg	7.30 m	2.40 m	4 demi 706	11 5/15	Hyd.	0.98	Jack leg	adjustable
RP B 10000	13000 kg	6.10 m	2.40 m	Bogie 808	135/75 430.9	Hyd.	1.03	Jack leg	Spring drawbar
RP B 10000	13000 kg	7.30 m	2.40 m	Bogie 808	135/75 430.9	Hyd.	1.03	Hyd.	Spring drawbar
RP B 13000	16400 kg	8.10 m	2.40 m	Bogie 908	15*22.5	Hyd.	1.15	Hyd.	Spring drawbar

Site web : [www.roche-trailers.com](http://www.roche-trailers.com)- E-Mail : [contact@roche-trailers.com](mailto:contact@roche-trailers.com)

Design & Production : [Eric CHAUVIN](#)