



Manufacturer of made-to-measure agricultural trailers since 1945

## OUR SMALL EQUIPMENT

### Water tun on wheeled chassis from 600 to 6000 litres



### Between-wheel tool carrier for tractors

3 hydraulic functions



### Sander on a tractor lift

Sand the grass for stands or on paths and tracks. Adjustable outflow.



### DO YOU NEED SPECIAL MODELS ?

All our catalogues are not exhaustive.

On request, we can adapt our models to the dimensions which you require !

## The little train

Transport of bins in the calibration sites



## Tumbril 3000 for multi purpose



## Pipe-carrying trailer

Transport of 9m long watering pipes  
Capacity: approx. 10/12 hc with removable heightening plates



## Pipe-carrying trailer with 2 floors (model 7m50)



## Box carrying trailer for watering pipe (model 6 m)



## Multi-purpose open carrier trailers

16400 kg of Total.LoadedWeight

Reference 908 axle bogie if available as an option

Hydraulic arm with hook



## Trailer for placing on the ground

Transport of carried tools or bin transport, dimensions according to customer requirements.



### DO YOU NEED SPECIAL MODELS ?

All our catalogues are not exhaustive.

On request, we can adapt our models to the dimensions which you require !

# Trailers for micro tractor - Parks

## Standard equipment :

- Drop down and removable dropside
- Back removable dropside support
- Tipping by hydraulic jack ordering from the tractor by flexible
- Dolly wheel
- Lighting
- Adjustable towing system

## Options :

- Three-way tipping trailer
- Wire netting heightening plate
- Wire netting roof
- Pump at hand instead of flexible
- Pneumatic more wide - consult us

TYPE	Live load	Empty weight	Platform	Dropside height	Wheels	Axle	Height above ground	Brake
R 150	1 500	385	2,50 x 1,32	0,38	185x14 (rech) ou similar	45	0,81	Méc.
R 200	2 000	395	2,50 x 1,32	0,38	205x15 (rech) ou similar	50	0,83	Méc.
R 250	2 500	715	3,00 x 1,50	0,50	205x16 (rech) ou similar	50	0,83	Méc.
R 300	3 000	730	3,00 x 1,50	0,50	10.0/75-15.3 10 ply	50	0,83	Méc.



## Mechanical digger



N°1 : 1,18 size. : 0,97x0,95x0,55 (vol. 0,51)  
1m cut - 1,18 overall width

N°2 : 1,28 size. : 1,07x0,95x0,55 (vol. 0,56)

N°3 : 1,38 size. : 1,17x0,95x0,55 (vol. 0,61)

N°4 : 1,45 size. : 1,26x0,95x0,55 (vol. 0,66)  
1,30m - 1,45 overall width

## Civil Engineering Skip



## MACHINE CARRIES TRAILERS

### Fruit trailer with loading ramps – PTC 3700 kg et 5990 kg RFN2 3000

RPCB 3500



#### Standard equipment : modèle 1 (PTC 3700 kg)

- platform 3,50x1,25
- wheel 10.0/75-15.3
- dolly wheel
- lightong
- mechanical brake
- loading ramps for tractor
- stabilizing feet

#### Standard equipment : modèle 2 (PTC 5990 kg)

- platform 4,00 x 1,85
- wheel 11.5/15 14 ply
- dolly wheel
- lighting
- mechanical brake
- loading ramps
- lateral corner iron de 80 mm in front and behind wheels
- stabilizing feet

### Platform trailers « tank carry » – PTC 7600 kg ( RP2 6000 )



- platform 5,08 x 1,85
- wheel 13.65/18
- mechanical and hydraulic brake
- lighting on the side escamotable

- lateral screw support

### Platform trailer at hydraulic incline – PTC 8700 kg ( RP2 7000 )



- platform de 6,00 x 2,40
- 4 wheels swinging arm 10.0/65x16 14 ply
- hydraulic support with pump with hand

- hydraulic brake
- lighting incorporated into the back crossbar
- fixe hitch
- releveage by 1 hydraulic jack double effects

### Tipping platform trailer machine carries – PTC 13000 kg ( RPB4 13000 )



- platform 6,18 x 2,45
- 4 wheels 13.65/18 16 ply
- jack leg
- hydraulic and mechanical brake
- axle swinging arm 808

- lighting
- fixe hitch
- releveage by 2 hydraulic jacks double effects

Site web : [www.roke-trailers.com](http://www.roke-trailers.com) - E-Mail : [contact@roke-trailers.com](mailto:contact@roke-trailers.com)  
Design & Production : [Eric CHAUVIN](#)