

ROCHE

AOUSTE -26- FRANCE

PERE & FILS



SARL ROCHE Père et Fils

Quartier Mivoie
26400 AOUSTE SUR SYE
Tél.: +33 4 75 25 14 72
Fax : +33 4 75 25 00 30

Manufacturer of made-to-measure agricultural trailers since 1945

TRAILERS FOR WINE-GROWERS



**Hydraulic tipping
inter-row
tumbrils**

Standard equipment :

- Screw support
- Adjustable-height hitch
- Lighting

2500 litres	Dropdown heightening plates	Wheels 225*15	Length : 2.50 m	Width : 1.30 m
3000 litres	Dropdown heightening plates	Wheels 225*15	Length : 3.00 m	Width : 1.30 m

OPTIONS :

- Dolly wheel
- Turning ring
- Stainless steel vat
- Wheel size 10.0/75/15

DO YOU NEED SPECIAL MODELS?

All our catalogues are not exhaustive.
On request, we can adapt our models to the dimensions which you require !



Marc – Tub



2-wheel tipping one-piece body trailers for wine-growers

Standard equipment :

- Dolly wheel
- Adjustable towing system
- Lighting
- Drop-down heightening plates



R 20	2000	700 Kg	2500 Kg	2.50 m	1.50 m	0.50 + 0.25	50	225/15	Dolly wheel
R 30	3000	750 Kg	3000 Kg	3.00 m	1.50 m	0.50 + 0.25	50	10/15	Dolly wheel



2-wheel tipping leakproof trailers for wine-growers

Standard equipment :

- Adjustable towing system
- Metal platform
- Removable leakproof open carrier
- Dolly wheel
- Mechanical brake
- Complete lighting

OPTIONS :

- Turning ring
- Drop-down heightening plates
- Stainless steel vat



2-WHEEL TIPPING TRAILERS, Leakproof for wine-growers with platform and vat										
TYPE	Live load (Kg)	Empty weight	Litres	Length (m)	Platform width	Overall width	Dropside height	Axle	Tyres	Front support
RBE 2	2500	650	2500	2.50	1.20	1.50	0.60	50	225/15	Dolly wheel
RBE 2	3000	750	3000	3.00	1.30	1.50	0.60	50	10/15	Dolly wheel
RBE 2	3500	900	3800	3.00	1.30	1.70	0.60	50	10/15	Dolly wheel

**2-wheel rear-tipping
one-piece bodied
balanced full trailers**



Standard equipment :

- Adjustable coupler head
- Complete lighting
- Without backward movement
- One-piece body
- Leakproof for grape harvest

OPTIONAL EXTRAS :

- Double bottom for grape harvest
- Anti-wave edge for grape harvest
- Hoops for a covering sheet
- Turning hitch
- Automatic opening of the door by tipping the open carrier
- par basculement de la benne
- Stainless steel body



REAR-TIPPING 2-WHEEL BALANCED FULL TRAILERS WITH ONE-PIECE BODY										
TYPE	Live load	Empty weight	Length	Overall width	Board height	Axle	Tyres	Brake	Front support	Hecto-litres
RBM2 3500	3500	900	3.10	1.60	0.80	50	10/15 10 ply	Mec.	Dolly wheel	38 hl
RBM2 4001	4000	1050	3.50	1.80	0.80	60	10/15 10 ply	Mec.	Dolly wheel	48 hl
RBM2 4002	4800	1150	3.50	2.00	0.80	60	11.5/15 14 ply	Mec.	Dolly wheel	53 hl
RBM2 4800	4800	1250	4.00	2.00	0.80	60	11.5/15 14 ply	Mec.	Dolly wheel	61 hl
RBM2 5500	5500	1450	4.00	2.20	0.80	70	13.5/75 430.3	Hydr.	Jack leg	68 hl
RBM2 6500	6500	1550	4.00	2.30	1.00	70	13.5/75 430.3	Hydr.	Jack leg	88 hl

Grape harvest elevators trailers with direct outflow



Standard equipment :

- Elevation height relative to the ground or hatch: R250 SDE=1.80 m -R400 SDE=2.00 m -R500 SDE=2.10 m
- Driven by a hydraulic motor reducer at 13 to 29 rpm
- Work rate 7 to 16 tons/hour (the hydraulic installation is the responsibility)

OPTIONAL EXTRAS :

- Electric motor reducer (screw turning at 18 rpm), work rate 9 to 11 tons/hour (the electrical installation is the customer's responsibility)
- Stainless steel screw
- Stainless steel body
- Control at the rear with a notched distributor and a reverser

TYPE	Capacity	Body length	External width	Total height	Axle	Tyres	Brake	Track
R 250 SDE	25 HL	2.50	1.30	1.55	50	225*15	Mec.	1.20
R 300 SDE	30 HL	2.75	1.50	1.60	50	10.0/75/15	Mec.	1.20
R 400 SDE	40 HL	3.00	1.90	1.75	60	11.5/80/15	Mec.	1.70
R 500 SDE	50 HL	3.00	2.00	1.90	60	11.5/80/15	Mec.	1.70

Vine shoot gatherer

9 and 10 teeth

Equipped with single acting or double acting hydraulic tongs.

9 tooth model,
overall width 1 m 27

10 tooth model,
overall width 1 m 62





GRAPE HARVEST SCOOP 800 litres 3 points

Overall width: 1.10 m
Elevation height: approximately 1.90 m
Dropside 18 cm



**Elevating open carriers
One-piece body
or removable dropsides**



DO YOU NEED SPECIAL MODELS ?

All our catalogues are not exhaustive.

On request, we can adapt our models to the dimensions which you require !



TYPE	STANDARD EQUIPMENT					Adjustable drawbar, lighting, fixed ring				
	Live load	Length (m)	Width (m)	Elevation (m)	Dropside height	Support	Wheels	Axle	Brake	
E 2	3000	3.00	1.50	1.90	0.50	Dolly wheel	10/15	50	Mec.	
E 2	4800	3.50	2.00	2.00	0.50	Dolly wheel	11.5/15	60	Mec.	
E 2	4800	4.00	2.00	2.50	0.50	Jack leg	11.5/15	60	Mec.	
E 2	6000	4.00	2.20	2.50	0.50	Jack leg	13,65/18 16 ply	70	Hydr.	
E 2	8000	4.00	2.20	2.50	0.50	Jack leg	15.22.5	80	Hydr.	

Row-straddling spreaders

ABSOLUTELY UNIQUE

- Two lateral body units situated on the wheels give it unique stability in the vineyards on hillsides
- Its clearance makes for easy handling at the ends of the rows
- Spreads in two rows of vines and centralizes the spreading well
- Hydraulically controlled directional drawbar



Manure spreaders for wine-growers Flared one-piece body

Standard equipment :

- Screw support
- Adjustable-height hitch
- Lighting
- Fixed ring
- Protection grille
- Universal joint

OPTIONS :

- Turning ring
- Protective shutters or cover
- Variable track
- Directional axle controlled hydraulically from the tractor
- Hitch on a lift arm
- Vertical rotors only, 1.20 internal width.
- Other widths and lengths can be requested by the customer



TYPE	Live load	Empty weight	Length (m)	Int. width	Overall width	Conveyor belt ch Ø10	Dropside height	Axle	Tyres	Brake	Support
REV 2 1500	1500	600	2.50	0.80	1.07	2 ch	0.60	50	200/60*14.5	Mec.	Dolly wheel
REV 2 1800	1800	620	2.50	1.00	1.27	2 ch	0.60	50	205/15	Mec.	Dolly wheel
REV 2 2500	2500	850	3.00	1.30	1.57	2 ch	0.60	50	225/15	Mec.	Dolly wheel

ROW-STRADDLING TRAILER

Standard equipment ::

wheel 10.0/75-15.3
screw support
lighting
mechanical brake

platform 2.10 x 3.20
front and side board 0.40 serving as passerelle
hydraulically drawbar
turning hitch



Site web : www.roche-trailers.com - E-Mail : contact@roche-trailers.com
Design & production : [Eric CHAUVIN](#)
